

SAFETY DATA SHEET

FOAMMASTER® Defoamer

Date of Issue: 16 December 2021

1. SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION

Chemical name of active ingredient(s): Polymethylsiloxane

Recommended use: Defoaming agent Supplier: UPL New Zealand

UPL New Zealand Limited PO Box 51584, Pakuranga

Auckland

Phone 0800 100 325 www.upl-ltd.com/nz

Emergency telephone number: 0800 CHEM CALL (0800 243 622) 24 Hours

2. HAZARDS IDENTIFICATION

Hazard Classification: 6.4A, 9.1C Required identification Details: WARNING:

> Keep out of the reach of children. Read label carefully before use.

> Keep out of the reach of children.

Wear rubber or impervious gloves and goggles when mixing or

working with concentrate.

Wash thoroughly with soap and water after work and before eating

%

and smoking.

CAS No.

Do not wear contaminated clothing.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation Information on hazardous ingredients

	67 (6 116	70
<u>Hazardous:</u>		
Glycerine	56-81-5	5-10%
Non-hazardous:		
Siloxane Polyalkylenoxide	Trade secret	1-5%
Copolymer Polyalkylenoxide	Trade secret	10-30%
Silica filled, Silicone Oil	Trade secret	10-30%
Water	7732-18-5	60-90%

4. FIRST-AID MEASURES

Description of necessary first aid measures:

General information: First-aid measures

Common name

Inhalation: Treat symptomatically

Ingestion: Do not induce vomiting. If victim is conscious, give 2 glasses

Issued by UPL New Zealand Limited Page 1 of 5
Product FOAMMASTER (ES639)

of water. Do not give anything by mouth to an unconscious

person.

Skin contact: Wash off with soap and water. If skin irritation occurs: Get medical

advice/ attention

Eye contact: Remove contact lenses, if present and easy to do. Rinse Cautiously

with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

First Aid Facilities:

Notes to a physician: Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

HAZCHEM Code:

Fire/Explosion Hazard:

ERP Guide No:

Extinguishing media:

Hazardous thermal (de)composition

products:

All standard extinguishing agents are suitable.

After evaporation of water, residue can burn to produce:

Oxides of carbon, oxides of silicon, formaldehyde. Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient quantities can act as an asphyxiant. Acute over-exposure to the products of combustion may result to irritation of the respiratory tract. This product contains methylpolysiloxanes which can generate

formaldehyde at approx 300°F (150°C) and above, in atmospheres that contain oxygen. Formaldehyde is a skin and respiratory

sensitizer, eye and throat irritant, acute toxicant and potential cancer

hazard.

2W

Specific methods:

Protection of fire-fighters: Fire fighters must wear NIOSH/MSHA approved positive pressure

self- contained breathing apparatus with full face mask and full

protective clothing.

Other Information:

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Wear protective equipment; chemical proof gloves, eye protection

and full-length clothing.

Environmental precautions: Prevent entry of product/run-off into drains and waterways.

Methods for cleaning up: Wipe, scrape or soak up in an inert material and put in a container for

disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear protective equipment as specified in protective

equipment section.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes. Keep out of the reach of children.

Do not freeze. Stir well before using.

May generate formaldehyde at temperature greater than 300°F

(150°C). See section 10 MSDS for details.

Safe Storage: Store in original container, tightly closed. Recommended storage

between 35°F (2°C) and 80°F (26°C)

Record Keeping:
Approved Handler:

Tracking:

Packaging materials:

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Guidelines

Issued by UPL New Zealand Limited Page 2 of 5 Product FOAMMASTER (ES639)

Tolerable Exposure limit:

Exposure Standards: NA **Exposure Standards outside the workplace:** NA

Engineering measures

Exposure control measures: Eyewash stations; showers; ventilation and other of forms of

engineering controls are preferred for controlling exposures.

Respiratory protection may be needed for non-routine or emergency

situations.

Personal Protective Equipment Detail specifications for equipment:

Respiratory system: Respiratory protection should be worn if a large spill occurs.

Respiratory protection must be provided in accordance with

OSHA regulations.

Skin and body: Wear suitable protective clothing and eye/face protection.

Hands: Impermeable or chemical resistant gloves.

Safety glasses with side shields. Eyes: General hygiene: Wash thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Colour, Odour. Opaque liquid. Faint odour.

No data available

Vapour Pressure: >20

>100°C; >211°F (estimated) **Boiling Point:**

Flash Point:

Freezing/Melting point: 0°C; 32°C (approximately)

Solubility in water: 20°C Specific gravity or density (WATER=1): 1.03 Relative Density (AIR=1): >1

Flammable limits:

Octanol/water partition coefficient:

Explosive Properties: Oxidation Properties:

Other:

10. STABILITY AND REACTIVITY

Stability: Stable Conditions to avoid: None known

Materials to avoid: None currently known

Hazardous Decomposition After evaporation of water, residue can burn to produce:

Oxides of carbon, oxides of silicon, formaldehyde. Carbon monoxide Products: is highly toxic if inhaled; carbon dioxide in sufficient quantities can act

> as an asphyxisnt. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. This product contains methylpolysiloxanes which can generate formaldehyde at

approximately 300 □ F (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer. eye and throat irritant, acute toxicant, and potential cancer hazard.

Will not occur.

Hazardous Reactions:

Hazardous polymerization:

11. TOXICOLOGICAL INFORMATION

Acute toxicity - Oral: No data available

Issued by UPL New Zealand Limited Page 3 of 5 Product FOAMMASTER (ES639)

Acute toxicity - Dermal:No data availableAcute toxicity - Inhalation:No data available

Inhalation and Ingestion:

Skin irritation:No data availableEye irritation:No data available

Respiratory Sensitization:

Sensitization:No data available
Mutagenic Effects:
No data available

Carcinogenic Effects: No adverse effects anticipated from available information.

Chronic toxicity

Repeat ingestion may cause damage to liver, kidneys, thyroid male

and female reproductive system and blood forming system.

Reproductive Effects: Mutagenicity: Carcinogenicity: Systemic Effects: Other Information:

12. ECOLOGICAL INFORMATION

Not an environmental Toxin

No data available

Fish:
Daphnia:
Bees:
Birds:
Soil:

Ecotoxicity:

Bioaccumulative potential: No data available

E.E.L and T.E.L.

13. DISPOSAL CONSIDERATIONS

Methods of disposal: Ensure unwanted product is used by another operator strictly in accordance with

label directions. Triple rinse container and add to spray tank and offer the container for recycling through the Agrecovery programme.otherwise

crush and bury in an approved landfill.

Empty container precautions: Do not contaminate bodies of water with chemical or empty container.

14. TRANSPORT INFORMATION - International transport regulations

UN number: This product is NOT classified as a Dangerous Good for transport in NZ; NZS

5433:2012.

Hazchem

Classification Code: Packing Group: Marine Pollutant:

Proper shipping name: Not a Dangerous Good

International transport

regulations:

This product is not regarded as a dangerous good, according to the national and international regulations on the transport of dangerous goods.

MTQ (non-Commercial): Passenger Service Vehicle:

15. REGULATORY INFORMATION

Issued by UPL New Zealand Limited Page 4 of 5 Product FOAMMASTER (ES639) ACVM Registered Number: HSNO Approval Code:

Not an Agricultural Compound. Additives, Process Chemicals and Raw Materials (subsidiary) – **HSR002503**

16. OTHER INFORMATION

Additional information:

Original Issue Date: 18th September 2013 **Revision Date:** 16 December 2021

Replaces: ES518

Disclaimer EXCLUSION OF LIABILITY: PLEASE READ

This Safety Data Sheet is based on the most recent information available. To the extent permitted by law, users of this information accept that neither the manufacturer, UPL New Zealand Limited as distributor, nor any other distributor have any liability or responsibility whatsoever for any loss, damage or injury whether in contract or tort, whether direct, indirect or consequential howsoever arising in connection with the supply of these information.

FoamMaster® is a Registered Trademark of UPL New Zealand Limited, Auckland, N.Z.